



# LED QUICK SHIP PROGRAM

# LED HIGH BAY FIXTURES



- NEW center mount motion sensor option available.
- Increased 150 lm/watt efficacy on all models.
- All models stocked with black housing.
- IP65 waterproof.
- cULus and DLC listed.
- Multiple mounting adapters available.



## HB05B SERIES



SPECIFICATIONS	
BEAM ANGLE	110°
CERTIFICATIONS	cULus, DLC
CRI	>80
DIMMABLE	0-10V Dimming
LED TYPE	SMD2835
INPUT VOLTAGE	100-277V; 50/60Hz
OPERATING TEMP	-40°F~122°F
POWER FACTOR	>0.9
SURGE PROTECTION	Yes
THD	≤20%
WARRANTY	6 Years
WATERPROOF	IP65 Wet Location

## FIXTURE QUICK SHIP STOCK ORDERING

MODEL	WATTAGE	LUMENS	BASE	COLOR TEMP	WEIGHT (Net   Gross)	DIMENSIONS
GLL-HB05B-100W-RBCGD1-BH50	100 Watt	15,000 LM	O Ring	50 = 5000K	6.5 lbs   8.8 lbs	12.2"DIA x 7.28"H
GLL-HB05B-150W-RBCGD1-BH50	150 Watt	22,500 LM	O Ring	50 = 5000K	6.5 lbs   8.8 lbs	12.2"DIA x 7.28"H
GLL-HB05B-240W-RBCGD1-BH50	240 Watt	36,000 LM	O Ring	50 = 5000K	9.92 lbs   13.9 lbs	14.57"DIA x 7.91"H

ORDERING GUIDE & EXAMPLE FOR STOCK INVENTORY: GLL-HB05B-100W-RBCGD1-BH50  
 GLL = Green Lighting LED | HB05B = Product Series | Wattage | R = DAERMAY Driver | B = Lumileds 2835 | CG = Clear Glass Lens | D1 = Version Number | BH = Black Housing | 50 = 5000K

## ACCESSORY QUICK SHIP STOCK ORDERING

MODEL	DESCRIPTION
GLL-HB05B-FM-BRKT-S	FM Trunnion Mount for 100W & 150W
GLL-HB05B-FM-BRKT-L	FM Trunnion Mount for 240W
GLL-HB05B-Mtg Adapter(M10)	3/4" Conduit Mounting Adapter for 100W & 150W
GLL-HB05B-Mtg Adapter(M12)	3/4" Conduit Mounting Adapter for 240W
GLL-HB05B-OC	Occupancy Motion Sensor
GLL-HB05B-OC Remote	Remote Control for Occupancy Sensor



Mtg Adapter



FM BRKT



OC REMOTE